

## Material Safety Data Sheet

### 1. Identification of the substance and the company

#### 1.1 Identification of the substance

Trade name JOLLY SMAK VERNICE  
Description/Use FOR USE ON PAINT, GLUE, INK, TAR, LIPSTICK, BALL-POINT PEN STAINS

#### 1.2 Identification of the company

Company name TINTOLAV s.r.l.  
Address Via Massimo D'Antona, 7  
Postal town and country 10028 TROFARELLO (TO)  
ITALY  
tel. +39 011/6496827  
fax +39 011/6496742  
tel. +39 02/66101029  
Emergency telephone number: Ospedale Niguarda (MI), Poison prevention centre

### 2. Composition / Information on the ingredients

Hazardous components	CAS-No. EINECS-No. ELINCS-No.	Symbol(s)	R-phrases	Concentration
Surface-agent not ionic acetato di butile	123-86-4 204-658-1	Xi Xi	R22/R41/R38 R 10/ R 66/R67	< 30% Tra 15% e 30%

### 3. Hazards identification

Risk of serious eye injuries.  
The exposure to vapors may cause dryness and cracks of the skin.  
Inhalation of vapors may cause drowsiness and dizziness

### 4. First aid measures

Contact with skin:  
Wash with plenty of water and soap.  
Contact with eyes:  
Wash immediately with water for at least 15 minutes, taking your eyes open and consult your doctor.  
Inhalation: Remove the person from the polluted and keep at rest in an aerated  
OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.  
Ingestion: Rinse your mouth with water. Do not induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

### 5. Fire-fighting measures

Can produce fumes containing carbon dioxide and carbon monoxide in fires large  
Recommended extinguishers:  
Powder, foam, sand, water spray.  
Extinguishers not to be used:  
None  
Protective equipment:  
Use protection for the respiratory tract.

## 6. Accident release measures.

It can make the floor slippery.

Individual Measures: Wear gloves, rubber boots, goggles.

Environmental precautions: Contain losses with earth, sand and materials inert materials cleanliness: If you can collect the product for reuse or absorb with inert material. Wash and materials affected area with water. Do not dispose of washing water to surface waters

## 7. Handling and storage

Terms of storage: Store at temperatures below 40 ° C

Directions for the premises: Fresh and adequately ventilated. Power plant safety precautions handling: Avoid contact with skin and eyes (see next paragraph)

Materials compatible: Steel Polypropylene - Steel vitrified --

## 8. Exposure controls / personal protection

Respiratory Tract: unnecessary they are complied with the exposure limit values. Skin: gloves and boots waterproof and resistant to solvents. Apron rubber

Eyes: Glasses Splashguards

Component with a value limit to be respected in the workplace: N butilacetato TLV-150 ppm 713 mg/m3

## 9. Physical and chemical properties

Appearance and colour	Liquid yellow
Odour	particular
pH	7.0
Flash point	< 10° C
Auto ignition temperature	>61° C
Solubility in water	Yes and in halogenated solvents too
Freezing point	>0° C

## 10. Stability and reactivity

Conditions to avoid: Stable under normal conditions

Reactions dangerous: it can react with a strong oxidizing

Hazards from decomposition: Not decomposes under normal conditions

Decomposition > 200 ° C

## 11. Toxicological information

Not classifiable as "harmful if swallowed" according to the concentration of substances in the preparation. It can, however, cause irritation to the mouth and digestive tract first. It can produce skin irritation after a prolonged or repeated contact. It can cause serious permanent damage to the eyes.

## 12. Ecological information

Use the second best working practices rather than disperse into the product.

It can be toxic in respect of fish and other aquatic organisms.

Do not use in cleaning operations or washing in which discharges may reach the aquatic environment

Product to be used exclusively in the process of dry cleaning.

## 13. Disposal considerations

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

## 14. Transport information

Road (ADR): not dangerous

## 15. Regulatory information

D.Lgs.3/2/1997 n.52 and subsequent adjustments (classification, packaging and labelling hazardous substances)

### **Xi irritant R 41 RISK OF SERIOUS INJURY EYEPIECES**

The exposure to vapors may cause dryness and cracks of the skin.

Inhalation of vapors may cause drowsiness and dizziness.

Protect your eyes and face

In case of contact with the eyes wash immediately with plenty of water and consult your doctor.

In case of contact with skin, wash immediately with plenty of water.

Do not breathe vapors.

Keep away from flames and sparks. Do not smoke.

Contains:

Surface-agent not ionic  
acetato di butile

123-86-4  
204-658-1

## 16. Other information

### **PRODUCT FOR ONLY PROFESSIONAL USE IN THE LAUNDRIES.**

Phrases R component of Chapter 2 (full)

R41 risk of serious eye injuries.

The R66 exposure to vapors may cause dryness and cracks of the skin.

R67 Inhalation of vapors may cause drowsiness and dizziness.

Flammable R10

R22 Harmful if swallowed

The information contained herein is given in good faith and to the best of our current knowledge;  
However, no explicit or implicit guarantee is provided.

Customers should make sure the suitability of the product for the purpose for which it is used.