



Snack & Food



# SNAKKY RESTYLING





**SNAKKY RESTYLING** is the new aesthetically and technically renewed model of the Snakky vending machine. Perfectly suitable for medium-size locations, Snakky Restyling can offer an appealing, sturdy but elegant design, matchable with the one of Kikko Restyling:

- metal side panel
- user's interface area with black plastics
- lock fitted on the metal part

### TEMPERATURE

Guaranteed temperatures at 32°C and 65% humidity:

- Uniform (5°-8°C)
- Stratified (10°-15°C snack area, 5°-7°C C&B area)

### SAFETY

- Lock reinforced by a bush
- Closure by means of a sliding bar with two hooking points

### ELECTRONICS

- 16 bit-electronics with in-built 4 Mb Flash Eprom
- Management of the setup files and statistical data by means of Up-Key

### PAYMENT SYSTEMS

Payment systems can be easily installed in the renewed user's interface area. The presence of pre-cut panels will facilitate any kind of action in this area. Snakky Restyling is pre-set for the installation of systems with Executive and MDB protocol as well as for the installation of validators.

The following can be also fitted at the same time:

- change giver coin mechanism / validator
- bill acceptor
- cashless system with key or card.



L294U00

### ACCESSORIES

- Photocell kit (as standard)
- Coin box lid kit
- Wall-fastening bracket kit
- Master / slave kit
- Lift-up kit
- Bidirectional drawer motors kit
- Keypad protection kit
- Infrared kit
- RS232 jack Kit
- GSM kit



### EXAMPLES OF POSSIBLE CONFIGURATIONS

4 snack trays				6 snack trays			
12 selections / 270 products				27 selections / 338 products			
1 bottle tray							
6 selections / 36 products							
1 can tray							
6 selections / 36 products							
8	8	8	200 mm	10	10	10	200 mm
8	8	8	157 mm	13	13	13	197 mm
13	13	13	107 mm	13	13	13	157 mm
19	19	19	117 mm	13	13	13	127 mm
6	6	6	234 mm	13	13	10	134 mm
6	6	6	117 mm	10	8	8	134 mm

- Snack
- Bottles 0,5 l PET
- Cans 0,25/0,33 l

The numbers in the table indicate the product capacity

### CHARACTERISTICS

Height	1700 mm
Width	707 mm
Depth	860 mm
Overall depth with door open	1335 mm
Weight	190 kg ca.
Power supply voltage	230 V
Power supply frequency	50 Hz
Absorbed power	345 W
Maximum operating conditions	32°C - 65% R.H.

\*+10 - 10 mm

### POWER CONSUMPTION

For each hour of stand-by	151 Wh
Ambient temperature	20 °C
Refrigerated box temperature	8 °C

N&W Global Vending reserves the right to alter specifications without notice

### N&W GLOBAL VENDING S.p.A.

Via Roma, 24  
24030 Valbrembo (BG) Italia  
Tel. +39 035 606111  
Fax +39 035 606519



www.nwglobalvending.com